

OUR MOST ADVANCED COLD CLIMATE LINEUP YET



The New Standard for Heating
in the Extreme.

FX SERIES | DUCTLESS HEAT PUMP



OPERATES
DOWN TO
-37 °C[†]



100% HEATING
CAPACITY
DOWN TO -23 °C



SUPERIOR
SYSTEM
PERFORMANCE



INCREASED
ENERGY
EFFICIENCY



LOW GLOBAL
WARMING
POTENTIAL

[†]Includes tolerance. Typical units can operate in heating mode down to -36.7°C (above claims have been rounded to nearest integer of -37°C) depending on conditions.



Wide Capacity Range:
6,000 – 24,000 Btu/h

The **FX Series** features Mitsubishi Electric's most advanced Hyper Heat h2i technology, delivering year-round comfort in extreme climates with quiet, energy-efficient operation, 3D i-see Sensor control, and triple-action filtration.

UP TO **EER2: 21.45**

UP TO **SEER2: 35.00**

UP TO **HSPF2: 12.1**

UP TO **COP at 8 °C: 4.94**

**HEATS
TO
-37°C***



SINGLE-
ZONE

OR



MULTI-
ZONE



Industry-Leading Hyper Heat Plus Technology

ZUBA SINGLE PLUS



KEY FEATURES:

3D i-see Sensor

Intelligently personalizes airflow to occupants, optimizing energy savings and delivering unmatched comfort.

Built-In Wi-Fi Connectivity

Adjust comfort settings from anywhere in the world.

Smart Dry

New and improved advanced dehumidification mode.

Whisper Quiet Operation

Indoor units as low as 20 dB (A) ensure minimal noise for maximum comfort.

Advanced Multilayer Air Filtration

Ensures optimal air quality and prolonged equipment lifecycle.

Dual Barriers

Indoor unit coatings simplify cleaning, ensuring efficiency with minimal maintenance.

Base Pan Heater

Provides freeze protection and defrost drainage.



**SCAN the
QR Code**

To access full product
details and specifications



R-454B

10 YEAR
PARTS & COMPRESSOR
WARRANTY

VCSi
TECHNOLOGY



**MITSUBISHI
ELECTRIC**
Changes for the Better

MEM-202513-E © 2025 Mitsubishi Electric Sales Canada Inc. All rights reserved. Mitsubishi Electric reserves the right to modify the design of its products, their characteristics and the information contained in this literature. Specifications are subject to change without notice. Mitsubishi Electric, and the three diamond logo are registered trademarks of Mitsubishi Electric Corporation. Used with permission. *Includes tolerance. Units can operate in heating mode down to -36.7°C (above claims have been rounded to nearest integer of -37°C) depending on conditions. All test conditions are based on AHRI 210/240. *When installed and registered by a MEQ certified HVAC (Heating, Ventilation, and Air Conditioning) Installer. Certain conditions, restrictions and/or limitations apply. See warranty terms and conditions for complete details.