

COMFORT REDEFINED, AS PART OF OUR NEW ADVANCED LINEUP



Designed for the way you live

GX SERIES | DUCTLESS HEAT PUMPS & AIR CONDITIONERS



OPERATES
DOWN TO
-37 °C[†]



100% HEATING
CAPACITY
DOWN TO -15 °C^{††}



SUPERIOR
SYSTEM
PERFORMANCE



INCREASED
ENERGY
EFFICIENCY



LOW GLOBAL
WARMING
POTENTIAL

[†]Typical outdoor units will operate to the manufacturer's pre-programmed lock-out (outdoor ambient) temperature which ranges from -36.7°C to -18.5°C (-36.7°C has been rounded to the nearest integer, -37°C).

Product will resume operation at pre-programmed outdoor ambient temperature which ranges from -30°C to -10°C. (See product documentation for details.)

^{††}100% heating capacity at -15°C is for cold climate models only.



Wide Capacity Range: 9,000 – 36,000 Btu/h

The Mitsubishi Electric **GX Series** combines compact style with exceptional efficiency for cold climates, providing year-round comfort with quiet, energy-saving performance for every space.

UP TO
EER2: 15.40

UP TO
SEER2: 28.40

UP TO
HSPF2: 10.70

UP TO
COP at 8 °C: 4.84

COLD CLIMATE
HEAT PUMP

**HEATS
TO
-37°C[†]**

STANDARD
HEAT PUMP

**HEATS
TO
-25°C**

AIR
CONDITIONER

**COOLS
TO
-18°C**

SINGLE-ZONE



OR

MULTI-ZONE



Available in ZUBA Cold Climate models:

Zuba is a family of Cold Climate Heat Pumps featuring Hyper Heat Technology and was developed as a home heating and cooling system specifically for Canada.

**100%
HEATING
CAPACITY
AT -15°C^{††}**



KEY FEATURES:

Whisper Quiet Noise Levels

Indoor units are as low as 19 dB(A).

Multilayer Air Filtration

Ensures optimal air quality and prolonged equipment lifecycle.

Smart Dry

New and improved advanced dehumidification mode.

Built-In Wi-Fi Connectivity

Adjust comfort settings from anywhere in the world.

Dual Barrier Coating

Indoor unit coatings simplify cleaning, ensuring efficiency with minimal maintenance.

New Matte Finish

Scratch-resistant, long-lasting, and easy to clean.

Base Pan Heater

Provides freeze protection and defrost drainage.



**SCAN the
QR Code**

To access full product
details and specifications



R-454B

10 YEAR^{*}
PARTS & COMPRESSION
WARRANTY

VCSi
TECHNOLOGY

AHRI CERTIFIED
PARTS & COMPRESSION
WARRANTY



**MITSUBISHI
ELECTRIC**
Changes for the Better

MEM-202606-E © 2026 Mitsubishi Electric Sales Canada Inc. All rights reserved. Mitsubishi Electric reserves the right to modify the design of its products, their characteristics, and the information contained in this literature. Specifications are subject to change without notice. Mitsubishi Electric and the three-diamond logo are registered trademarks of Mitsubishi Electric Corporation. Used with permission. [†]Typical outdoor units will operate to the manufacturer's pre-programmed lock-out (outdoor ambient) temperature which ranges from -36.7°C to -18.5°C (-36.7°C has been rounded to the nearest integer, -37°C). Product will resume operation at pre-programmed outdoor ambient temperature which ranges from -30°C to -10°C. (See product documentation for details.). All test conditions are based on AHRI 210/240. ^{††}100% heating capacity at -15°C is for cold climate models only. ^{*}When installed and registered by a MEQ certified HVAC (Heating, Ventilation, and Air Conditioning) Installer. Certain conditions, restrictions and/or limitations apply. See warranty terms and conditions for complete details.